Hitachi **Chemical**



GPL 12520 12 52

GPL 12520 - 10 (10-12 20° Eurobat) 260 - CSB,




12 (6 U _. - 1.75 / 25° 52 A 20-17.20 500A (5 : -15° : -15° -15° +40° : -15° +40° 1485 25° 13.5 - 13.8 25° 15.6 A (), 14.4 - 15.0 25° 25° [′] 6 ABS (










, : () 228±2.5 138.4±1.5 201.3±2.5 206.3±2.5









			: A (25°)										
U _K /T	5	10	15	30	60	90	2	3	5	8	10	20	
1.60	225	155	116	67.2	38.5	27.7	21.7	15.2	9.66	6.35	5.17	2.66	
1.67	208	144	110	64.7	38.1	27.4	21.4	15.0	9.57	6.31	5.15	2.65	
1.70	195	138	108	63.6	37.8	27.3	21.3	14.9	9.53	6.28	5.14	2.64	
1.75	177	128	103	61.2	37.0	26.7	20.7	14.7	9.44	6.17	5.08	2.60	
1.80	159	119	95.7	58.7	35.7	26.0	20.3	14.3	9.22	6.04	4.94	2.56	
1.85	142	110	89.3	55.6	33.3	24.8	19.0	13.5	8.71	5.74	4.69	2.43	

							:	1	(25°)			Ì
U _K /T	5	10	15	30	60	90	2	3	5	8	10	20
1.60	2392	1684	1290	770	447	325	250	176	114	74.7	61.6	31.7
1.67	2176	1589	1235	748	445	323	247	175	113	74.4	61.2	31.6
1.70	2081	1540	1208	737	443	322	246	174	112	74.2	60.7	31.4
1.75	1914	1449	1160	710	434	315	242	171	111	73.9	60.3	31.3
1.80	1747	1359	1093	683	419	308	235	169	110	72.4	59.5	30.7
1.85	1584	1258	1031	649	395	295	223	161	105	69.6	56.7	29.4